PERFORMANCE MADE SMARTER



Programmable transmitter

5114A

– Input for RTD, TC, mV, linear resistance, mA, and V
– 3-port 3.75 kVAC galvanic isolation
– Current and voltage output
– Universal voltage supply
– 1- and 2-channel versions
– Loop supply > 17.1 V

Advanced features
- The 5114 transmitter can be configured using the PReset software and the Loop Link communications unit.

Application
- Jumper selectable inputs for current/voltage or temperature.
- Programmable current (0...100 mA) and voltage (0...250 VDC) inputs.
- Linearized, electronic temperature measurement.
- Conversion of linear resistance variation e.g, from solenoids and butterfly valves or linear movements with attached potentiometer.
- 17.1 VDC loop and 2.5 VDC potentiometer supplies.
- Automatic 4- / 3-wire or programmable 2-wire cable compensation.
- Configurable sensor error detection including NAMUR NE43.

Technical characteristics
- Active or Passive current output and selectable voltage output.
- Separation of circuits in PELV/SELV installations.

Applications



This page is automatically generated on the basis of information provided on www.prelectronics.com and affiliated websites. It is provided to you as a service and for information purpose only. While we have attempted to maintain the information as accurately as possible, the page may contain errors or omissions for which we disclaim any and all liability

Order:

Type	Version	Input	Channels
5114 A	Standard : A	RTD / TC / R / mA / V / mV : -	Single : A Double : B

Note! For TC inputs with internal CJC, remember to order the CJC connectors type 5910 / 5910 Ex (ch. 1) and 5913 / 5913 Ex (ch. 2).

Environmental Conditions

Operating temperature ..... -20°C to +60°C
Calibration temperature ..... 20...28°C
Relative humidity ..... < 95% RH (non-cond.)
Protection degree IP20

Mechanical specifications

Dimensions (HxWxD) ..... 109 x 23.5 x 130 mm
Weight approx. ..... 225 g
DIN rail type ..... DIN EN 60715/35 mm
Wire size ..... 0.13...2.08 mm^2 AWG 26...14 stranded wire
Screw terminal torque ..... 0.5 Nm

Common specifications

Supply

Supply voltage, universal ..... 21.6...253 VAC, 50...60 Hz or 19.2...300 VDC
Fuse ..... 400 mA SB / 250 VAC
Max. required power ..... 2.1 W / 2.8 W (1 / 2 ch.)
Max. power dissipation ..... 2.0 W

Isolation voltage

Isolation voltage, test / working ..... 3.75 kVAC / 250 VAC
PELV/SELV ..... IEC 61140

Response time

Temperature input, programmable (0...90%, 100...10%) ..... 400 ms...60 s
mA / V input (programmable) ..... 250 ms...60 s

Auxiliary supplies

2-wire supply (pin 44...42 and 54...52) ..... 28...17.1 VDC / 0...20 mA

Programming ..... Loop Link
Signal / noise ratio ..... Min. 60 dB (0...100 kHz)
Accuracy ..... Better than 0.05% of selected range
Updating time ..... 115 ms (temperature input)
Updating time ..... 75 ms (mA / V / mV input)
Signal dynamics, input ..... 22 bit
Signal dynamics, output ..... 16 bit
Auxiliary voltages: Reference voltage ..... 2.5 VDC ±0.5% / 15 mA
EMC immunity influence ..... < ±0.5% of span
Extended EMC immunity: NAMUR NE21, A criterion, burst ..... < ±1% of span

Input specifications

Common input specifications

Max. offset ..... 50% of selected max. value

RTD input

RTD type ..... Pt100, Ni100, lin. R
Cable resistance per wire ..... 10 Ω (max.)
Sensor current ..... Nom. 0.2 mA
Effect of sensor cable resistance (3-/4-wire) ..... < 0.002 Ω / Ω
Sensor error detection ..... Yes

TC input

Thermocouple type ..... B, E, J, K, L, N, R, S, T, U, W3, W5, LR
Cold junction compensation (CJC) ..... < ±1.0°C
Sensor error current ..... Nom. 30 µA
Sensor error detection ..... Yes

Current input

Measurement range ..... 0...100 mA
Min. measurement range (span) ..... 4 mA
Input resistance: Supplied unit ..... Nom. 10 Ω + PTC 10 Ω
Input resistance: Non-supplied unit ..... RSHUNT = ∞, VDROP < 6 V

Voltage input

Measurement range ..... 0...250 VDC
Measurement range ..... -150...+150 mV
Min. measurement range (span) ..... 5 mV
Input resistance ..... Nom. 10 MΩ (≤ 2.5 VDC)
Input resistance ..... Nom. 5 MΩ (> 2.5 VDC)
Input resistance ..... Nom. 10 MΩ (mV input)

Output specifications

Current output

Signal range ..... 0...20 mA
Min. signal range ..... 10 mA
Load (@ current output) ..... ≤ 600 Ω
Load stability ..... ≤ 0.01% of span / 100 Ω
Current limit ..... ≤ 28 mA
Sensor error indication ..... Programmable 0...23 mA
NAMUR NE43 Upscale/Downscale ..... 23 mA / 3.5 mA

Passive 2-wire mA output

Signal range ..... 4...20 mA
Load stability ..... ≤ 0.01% of span / 100 Ω
Max. external 2-wire supply ..... 29 VDC
Effect of external 2-wire supply voltage variation ..... < 0.005% of span / V

Voltage output

Signal range ..... 0...10 VDC
Min. signal range ..... 500 mV
Load (@ voltage output) ..... ≥ 500 kΩ

of span ..... = of the presently selected range

Observed authority requirements

EMC 2014/30/EU
LVD 2014/35/EU
RoHS 2011/65/EU
EAC ..... TR-CU 020/2011

Approvals

DNV Marine TAA0000101